

**Material Safety Data Sheet
Polycarbonate (Lexan)**

Section 1 – Chemical Product

Product Identifier: Lexan Resin
Product Description: Poly (Bishenol-A Carbonate) (CAS #111211-39-3)
Product Use: May be used to produce molded or extruded articles or as a component of other industrial products.

Section 2 – Composition/Information on Ingredients

This product consists primarily of high molecular weight polymers. Substances listed below are reportable hazardous ingredients as defined by the OSHA Hazard Communication Standard. Exposure limits, when available, are also listed.

Additional compositional data are provided in Section 15, Regulatory Information, subject to supplier notification requirements.

CAS Number	OSHA Units	ACGIH Units	Chemical Name
------------	------------	-------------	---------------

This product does not contain reportable hazardous ingredients as defined by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 3 – Hazards Identification

Emergency Overview:

Solid pellets with slight or no odor. Spilled pellets create slipping hazard. Can burn in a fire creating dense toxic smoke. Molten plastic can cause severe thermal burns. Fumes produced during melt processing may cause eye, skin and respiratory tract irritation. Secondary operations, such as grinding, sanding, or sawing, can produce dust which may present an explosion or respiratory hazard.

Potential Health Effects:

Eye:	Product may cause irritation or injury due to mechanical action.
Skin:	Pellets not likely to cause skin irritation.
Ingestion:	Not acutely toxic.
Inhalation:	Pellet inhalation unlikely due to physical form.

Chronic/Carcinogenicity:

NTP:	Not tested.
OSHA:	Not regulated.
IARC:	Not listed.

Melt Processing Health Effects: Molten plastic can cause severe burns.

Processing fumes may cause irritation to the eyes, skin and respiratory tract, and in cases of severe overexposure, nausea and headache.

Grease-like processing fume condensates on ventilation duct work, molds and other surfaces can cause irritation and injury to skin.

Medical Restrictions:

There are no known human health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing fumes.

Note:

Additives containing certain heavy metal compounds may be present. These ingredients are essentially bound in the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

Section 4 – First Aid Measures

Eyes:	Remove contact lenses at once. Immediately flush eyes well with copious quantities of water or normal saline for at least 20-30 minutes. If irritation persists, seek medical attention.
Skin:	Wash skin thoroughly with soap and water. Seek medical attention if rash or burn occurs.
Ingestion:	Not probable. If a large amount is swallowed, see medical attention.
Inhalation:	Not likely to be inhaled due to physical form.
Melt Processing:	For molten plastic skin contact, cool rapidly with water and immediately seek medical attention. Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.

For processing fume inhalation irritation, leave contaminated area and breathe fresh air. If coughing, difficult breathing or any other symptoms develop seek medical attention at once, even if symptoms develop at a later time.

For skin contact with fume condensate, immediately wash thoroughly with soap and water. If irritation develops seek medical attention.

Section 5 – Fire Fighting Measures

Fire Fighting:

Approved pressure demand breathing apparatus and protective clothing should be used for all fires. Water spray is the preferred extinguishing medium. This product will melt but will not be carried on the surface of water.

Extinguishing Media:

Water spray and foam. Water is the best extinguishing medium. Carbon Dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.

Hazardous Combustion Products:

Hazardous combustion products may include intense heat, dense black smoke, Carbon Monoxide, Carbon Dioxide and Hydrocarbon fragments.

Flash Point:	Not applicable
Lower Flammable Limit:	Not established
Upper Flammable Limit:	Not established
Auto-ignition:	1166°F (630°C) (estimated)
Conditions of Flammability:	Requires a continuous flame source to ignite
Explosion Data:	
Impact Sensitivity:	Not sensitive to mechanical impact
Static Discharge:	Not sensitive to static discharge (See Handling and Storage)

Section 6 – Accidental Release Measures

General:

Sweep or gather up material and place in proper container for disposal or recovery. (see Disposal Information)

Section 7 – Handling and Storage

Handling:

Follow recommendations on label and in processing guide. Prevent contact with skin and eyes. Use good industrial hygiene practices. Provide adequate ventilation. Secondary operations such as grinding, sanding or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation; employ bonding, grounding, venting and explosion relief provisions in accordance with accepted engineering practices.

Storage:

Store in a dry place away from moisture, excessive heat and sources of ignition.

Section 8 – Controls/Personal Protection

Engineering Controls:

A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, duct work and other surfaces using appropriate personal protection. For powders and residual dusts refer to Handling and Storage section.

Ventilation requirements must be locally determined to limit exposure to processing fumes in the workplace.

Personal Protection:

Eye/Face:	Wear safety glasses with side shield or chemical goggles. In addition, use full face shield when cleaning processing fume condensates from hoods, ducts and other surfaces.
-----------	---

Skin:	When handling pellets avoid prolonged or repeated contact with skin. When melt processing product wear long pants, long sleeves, well insulated gloves and face shield when applicable. Use appropriate protective clothing, including chemical resistant gloves, to prevent any contact with processing fume condensates.
Respiratory:	When processing fumes are not adequately controlled, use respirator approved for protection from organic vapors and acid gases. When dust or powder from secondary operations, such as grinding, sanding or sawing, are not adequately controlled use respirator approved for protection from dust.

Section 9 – Physical and Chemical Properties

Physical State:	Solid
Odor and Appearance:	Plastic pellet with slight odor
Boiling Point:	Not applicable
Melting Point:	See Comment below
Vapor Pressure (mmHg):	Negligible
Vapor Density (air=1):	Not applicable
Specific Gravity (water=1):	>1
Water Solubility:	Insoluble
% Volatiles:	Negligible
pH:	Not applicable
Odor Threshold:	Not established
Evaporation Rate:	Negligible
Coefficient Water/Oil Dist:	Not established
Comment:	This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.

Section 10 – Stability and Reactivity

Stability:	Stable under recommended conditions of storage and handling.
Reactivity:	Not reactive under recommended conditions of handling, storage, processing and use.
Conditions to Avoid:	Do not exceed melt temperature recommendations in product literature. In order to avoid auto-ignition/hazardous decomposition of hot thick masses of plastic, purgings should be collected in small, flat shapes or thin strands to allow for rapid cooling and quench in water. (See Exposure Controls/Personal Protection section for respiratory protection advice).
Hazardous Decomposition:	Processing fumes evolved at recommended processing conditions may include trace levels of Phenol, Alkylphenols, and Diarylcarbonates.

Section 11 – Toxicological Information

Product:

Eye:	Product not considered primary eye irritant. When similar products, in finely divided form, were placed into the eyes of rabbits, slight transient redness or discharge occurred – consistent with the expected slightly abrasive nature of the resin particles.
Skin:	Product not considered primary skin irritant. Draize Skin Primary Irritation Score (rabbit) for similar products, in finely divided form, for a 24-hour exposure is 0. Not expected to be a skin sensitizer based on results of Modified Buehler Guinea Pig Sensitization Test from similar products. Dermal LD50 (rabbit) >2 g/kg, estimated.
Acute Oral:	Oral LD50 (rat) >5 g/kg, estimated
Acute Inhalation:	Processing fumes from similar products are not considered toxic. In acute inhalation tests, laboratory rats were exposed to processing fumes at concentrations exaggerating those that would likely occur in workplace situations. No deaths or signs of toxicity, except transient irritancy in some cases, were noted during the 6-hour fume exposure tests. There were no distinct or consistent treatment related tissue or organ changes noted in gross necropsies.
Subchronic:	In subchronic testing, the base resin was considered physiologically inert when fed to rats for 8 weeks at a dietary level of 6%.

Section 12 – Ecological Information

General:	Not expected to present any significant ecological problems.
----------	--

Section 13 – Disposal Information

RCRA Hazardous Waste:	Product is not a RCRA hazardous waste
Waste Disposal:	Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification

Section 14 – Transportation Information

DOT Hazard Class:	Not regulated
Proper Shipping Name:	Not regulated
Identification Number:	Not listed
TDGA:	Not listed

Section 15 – Regulatory Information

Listed below are chemical substances subject to supplier notification requirements. The percentages, when present, represent average values.

CAS Number	EPCRA	WHMIS	NPRI	CA-65	FL RI
Chemical Name	313%	%	%	%	

This product does not contain reportable quantities of substances subject to supplier notification.

TSCA Status:	This product complies with the Chemical Substance Inventory requirements of the US EPA Toxic Substances Control Act (TSCA).
WHMIS Classification:	Not a controlled product.

Section 16 – Other

The above information and recommendations are believed accurate and reliable. Because it is not possible to anticipate all conditions of use additional safety precautions may be required. Seelye Acquisitions, Inc. makes no warranty, either express or implied, including merchantability and fitness.

<u>User Responsibility:</u>	Each user should read and understand this information and incorporate it into individual site safety programs in accordance with applicable hazard communication standards and regulations.
-----------------------------	---

Abbreviations:

ACGIH:	American Conference of Governmental Industrial Hygienists
CA-65:	California Proposition 65 (Safe Drinking Water & Toxic Enforcement Act)
CAS #:	Chemical Abstracts Service number
EPCRA 313:	Emergency Planning and Community Right-to-Know Act, Section 313
FL:	Florida Right-to-Know Law, Substance List
OSHA:	The Occupational Safety and Health Administration
NPRI:	The Canadian National Pollutant Release Inventory
RCRA:	Resources Conservation and Recovery Act
RI:	Rhode Island Right-to-Know Law, Hazardous Substance List
WHMIS:	Canadian Workplace Hazardous Materials Information System